



AERUS

The Healthy Home Experts®

## Features ActivePure Technology proven to reduce viruses, bacteria, and other pathogens (full list of tested pathogens available below in “The Proof”)

### THE TECHNOLOGY

The Aerus® Beyond Guardian Air combines multiple complementary technologies, including HEPA, activated carbon, and ActivePure Technology. Patented ActivePure is an advanced surface and air purification technology. It has been proven to reduce over 99.9% of many common airborne and surface contaminants (list of tested pathogens can be found in “The Proof” section below).

**ActivePure does not replace the need to follow public health guidelines and should be used as complementary technology.**

### THE PROOF

In extensive unaffiliated lab testing, ActivePure® Technology has been proven to significantly reduce the following contaminants and pathogens:

- SARS-CoV-2 – RNA Virus
- H1N1 Influenza
- H5N8 Influenza
- Murine Norovirus
- PhiX-174
- MS2 Bacteriophage
- MRSA
- E. coli
- Salmonella enterica
- Legionella pneumophila
- Clostridium difficile
- Bacillus globigii
- Erwinia herbicola
- Listeria monocytogenes
- Candida auris
- Botrytis cinerea
- Sclerotinia sclerotiorum
- Aspergillus versicolor
- Aspergillus niger endospores
- Methicillin-resistant Staphylococcus epidermis
- Staphylococcus epidermidis

### THE BENEFITS

The Aerus Beyond Guardian Air provides surface decontamination and air purification without the use of ozone. It is an automated, proactive, and effective solution for your home or business.

- Portable, lightweight device
- No installation – plug-and-play solution
- Easy to use and low maintenance
- Proven effective against many common viruses, bacteria, molds, and fungi
- Reduces smoke, allergens, odors, and VOCs



View test results at [www.aerusonline.com/Scientific-Proof](http://www.aerusonline.com/Scientific-Proof)

[www.AerusOnline.com](http://www.AerusOnline.com)

# BEYOND<sup>®</sup>

## GUARDIAN AIR

### SPECIFICATIONS

Product Information	120V: 00634 Model: F159E 230V: 00648 Model: F159F Model F159E Meets California ozone emissions limit. CARB Certified
Technology Included	ActivePure <sup>®</sup> HEPA Filter Activated Carbon
Electrical	Input Voltage: 120 VAC 60 Hz Power Consumption: 23 Watts to 80 Watts Conforms to UL STD 867
Mechanical	Motor: 230 VAC; 0.28 Amp Airflow Rate: 75 CFM - 240 CFM
Weight & Dimensions	34 lbs (15.5 kg) 23" H x 20" W x 11" D (58.4 cm x 50.8 cm x 27.9 cm)
Operating Temperature	(Return Air) 30° F to 95° F (-1°C – 35°C)
Sound Level	Speed 1: 32 dB(A)      Speed 2: 39 dB(A) Speed 3: 46 dB(A)      Speed 4: 58 dB(A)
Recommended Maximum Coverage in a Contiguous Space <sup>1</sup>	Up to 2,500 sq. ft. (232m <sup>2</sup> ) depending on occupant density and other factors <sup>1</sup> . High density commercial not to exceed 1,000 sq. ft. (92m <sup>2</sup> ). For coverage in medical or health care environments, contact <a href="mailto:Medical@activepure.com">Medical@activepure.com</a> .
Warranty	Limited 5 Year Warranty (Terms & Conditions apply)



Contact Name: \_\_\_\_\_



Email: \_\_\_\_\_



Phone Number: \_\_\_\_\_

1. Assumes 8 foot ceilings. Solutions should be customized based upon a variety of factors including HVAC system capabilities and settings, air flows taking into account walls, air pressure, and doors, ambient air temperatures and humidities, variable density, known VOC concentrations, and other layers of protection.